Safety Data Sheet

SABRE Red Gel-Civilian

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910. 1200(g). Standard must be reviewed for specific requirements.

Quick Identifier

SECTION 1 - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME: SABRE Red GEL-Civilian SYNONYMS: Pepper Spray, OC Spray

CHEMICAL NAME: Oleoresin Capsicum (Red Pepper)

CHEMICAL FAMILY: Irritant Agent
PRODUCT USE: Personal Safety

MK-3-GEL-H-US; MK-3-GEL-H-US-JP; HC-14-CPG-BK-US; HC-14-CPG-PK-US; F15-TUSG; F15-BUSG, -02, -Q2; F15-BUSG-02-JP; F15-PUSG, -02, -Q2; F15-PUSG-02-JP; F15-MUSG; F15-MUSG-02-JP; M-35-GEL-FR; PGSP-01; PGSP-01-JP; D35-PG; P-22J-OC-US; P-22J-PK-US; FHP-01; SRU-HAPK; PFHM-80; PFHM-80-JP; PL-01-GEL; P-22-GEL-TQ, -GR; P-22G; P-22G-PAT; P-22G-JP; P-22J-OC-02, -GR; P-22J-PK-02; MK3-CFTG-BC; AM-ATH-01 (P-22J-OC); AM-ATH-02 (P-22J-PK-US); SE-MT-01, -JP; SE-BK-01, -JP; MK3-CFTG-BCGR; SE-BK-AMZ; SE-MT-AMZ; F15-BKOC-AMZ; F15-PKOC-

(P-22J-PK-US); SE-MT-01, -JP; SE-BK-01, -JP; MK3-CFTG-BCGR; SE-BK-AMZ; SE-MT-AMZ; F15-BKOC-AMZ; F15-PKOCAMZ; F15-MTOC-AMZ; F15-LGOC-AMZ; RU-22G; F15-PUSG-AMZ; DSGK-BK-AMZ; LED-22G-PK / LED-22G-PK-AMZ;

LED-22G-YW /LED-22G-YW-AMZ

Manufacturer's Name:SECURITY EQUIPMENT CORPORATIONEmergency Phone:800-325-9568Address:747 SUN PARK DRIVEOther Calls:636-343-0200City, State, ZipFENTON, MO 63026Fax Number:636-343-1318

Emergency Telephone Number for Infotrac: Tel.: +1-800-535-5053, Tel.: +1-352-323-3500

Fax: +1-352-323-0005

SECTION 2 - HAZARD IDENTIFICATION

GHS Pictogram:

MODEL #'s:





Signal Word: Warning

Hazard Statement(s)

H229 Pressurized container, may burst if heated

H315 Causes skin irritation
H319 Causes serious eye irritation
H335 May cause respiratory irritation

Precautionary Statement(s)

P102 Keep out of reach of children

P210 Keep away from heat / sparks / open flame / hot surfaces - NO SMOKING

P251 Pressurized container: Do NOT pierce or burn even after use

P302 + P352 IF ON SKIN: Wash with plenty of soap and water

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and

easy to do. Continue to rinse.

P337 + P313 IF EYE IRRITATION PERSISTS: Get medical advice / attention

P410 Protect from sunlight

P412 Do NOT expose to temperatures exceeding 50°C / 122°F

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical & common name(s) | Content(s) | OSHA TWA | ACGIH ILV | Carcinogen (Yes / No) |
|---|------------|----------|-----------|-----------------------|
| Oleoresin Capsicum (OC/Red Pepper) CAS# 8023-77-6 | 10%* | N/A | N/A | No |
| Water CAS# 7732-18-5 | 40 - 70% | N/A | N/A | No |
| Polysorbate 80 CAS# 9005-65-6 | 5 - 30% | N/A | N/A | No |
| Ethanol CAS# 67-17-5 | 2 - 10% | N/A | 200 ppm | No |
| Masamide CAS# 85526-23-8 | Marginal | | | No |
| Nitrogen (propellant) CAS# 7727-37-9 | ** | N/A | N/A | No |

Major Capsaicinoids are determined via A.O.A.C. Method 995.03. ** Ingredient volumes are trade secrets as defined in Hazard Communications ACT 29 CFR 1910.1200(g) Para 1 (1) end Appendix D to CFR 1910.1200(g).

SECTION 4 - FIRST AID MEASURES

Routes of Entry

Remove victim from contaminated area and remove contaminated clothing. Provide fresh air, **Emergency & First Aid Procedures:**

irrigate with copious amounts of cool water. Obtain medical advice if symptoms persist.

Remove from contaminated area immediately. Provide fresh air. If breathing is 1. Inhalation difficult, seek immediate medical attention. If the victim is not breathing, administer CPR and seek immediate medical attention.

Only exposed subject or EMS should remove subject's contact lenses. Irrigate with 2. Eyes cool water for 15 minutes, or until relieved. Seek medical attention if irritation

persists

Flush with cool water for 15 minutes. Wash with mild soap and water. Seek medical 3. Skin attention if irritation persists.

Unlikely route of entry. DO NOT INDUCE VOMITING. Rinse mouth with water. 4. Ingestion Ingest milk or water. Immediately call for medical help.

SECTION 5 - FIRE-FIGHTING MEASURES

Flammability Classification 16 CFR 1500.45: Non-Flammable; Electronic Immobilization Device Compatible

Flash Point: Auto-Ignition Temperature: N/A

Extinguishing Media: Halon, Carbon Dioxide, Dry Chemical or Water Special Fire Fighting Procedures: Wear respirator or self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: Smoke would be irritating to eyes and mucous membranes. Containers may burst in the heat of a fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Steps to follow if material is spilled Wipe up small spills with absorbent material. With large spills, use respiratory equipment, to avoid irritation,

and collect absorbent materials. or released:

If inside: Ventilate area and after absorbent process, wash area with soap and cold water

If outside: Stav upwind

Dispose of in accordance with current laws and regulations. Waste Disposal Method:

SECTION 7 - HANDLING AND STORAGE

Store upright in a cool, dry area. Avoid direct light and heat. Precautions to be taken in handling &

DO NOT expose to temperatures over 120° F / 50° C. storage: DO NOT puncture or incinerate container.

Other Precautions: Assure can is in a secure place to prevent accidental rupture.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Not normally required in well-ventilated areas, however, NIOSH approved respiratory protection may be

required when the material is used in confined areas. Avoid overexposure for long periods in enclosed areas. Respiratory Protection:

Ventilation: Yes

Protective Gloves: Suggested (not required)

Yes. Trainee exposure without protection in controlled training environment is acceptable. Eye Protection:

Other Protective Clothing/Equipment: Not required

Work/Hygienic Practices: Avoid absorption of product on clothing. If absorbed in clothing, remove and wash clothes at once. Do not eat,

drink, or smoke while handling product.

Provide ventilation if working in confined areas. **Engineering Controls:**

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

Appearance & Odor: Red/Orange in color. Odor is pungent Physical State: Liquid **Boiling Point:** 100° C (212° F) Specific Gravity (H20 = 1) ~1.0 @ 20° C Solubility in Water: Soluble Vapor Pressure: 140 PSI

SECTION 10 - STABILITY AND REACTIVITY

Unstable Conditions To Avoid Incompatibility (Materials To Avoid) N/A Stability

Stable X May Occur Hazardous

Polymerization: Will Not Occur Conditions To Avoid Hazardous Decomposition Products: N/A X

SECTION 11 - TOXICOLOGICAL INFORMATION

Standard Draize Test: Skin, rabbit, 500 mg Severity: Slightly Irritating Standard Draize Test: Eye, rabbit, 100 mg Severity: Mildly Irritating **ACUTE INHALATION LC50 (rat):** > 100.5 mg/L

SECTION 12 - ECOLOGICAL INFORMATION

This product has not been tested for environmental effects.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Methods:

Consult Federal, State, and Local Regulations

Evacuate contents in a safe area, & dispose of container.

SECTION 14 - TRANSPORT INFORMATION

DOT HM-181 INFORMATION

GROUND AIR

Proper Shipping Name:LTD. QTYAerosols, non-flammableHazard Class or Division:none2.2Identification Number:noneUN1950Packaging Group:nonenoneLabel(s) Required:none2.2 LTD. QTY

INTERNATIONAL TRANSPORTATION REGULATIONS

Regulations vary from country to country. Check regulations for your country.

GROUND AIR **OCEAN** LTD. QTY Aerosols, non-flammable Aerosols, non-Proper Shipping Name: Hazard Class or Division: ORM-D 2.2 2.2 UN1950 UN1950 **Identification Number:** none Packaging Group: none none none Label(s) Required: 2.2 LTD. QTY 2.2 LTD. QTY none

SECTION 15 - REGULATORY INFORMATION

GHS within the EU: The new classification & labelling system according to CLP regulation (EC) No 1272/2008

Health hazard symbol:

Signal Word: WARNING







aith nazard symbol:

Exclamation Mark Skin & Eye Irritation, Category 2

H-Codes

H315: Causes skin irritation

H319: Causes serious eye irritation

H229: Pressurized container: may burst if heated

H335: May cause respiratory irritation

P-Codes

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P251: Do not pierce or burn, even after use.

P302+P352: IF ON SKIN: Wash with plenty of water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. continue

insing.

P337+P313: If eye irritation persists get medical advice/attention.

P410: Protect from sunlight.

P412: Do not expose to temperatures exceeding 50 °C/122 °F.

TOXIC SUBSTANCES CONTROL ACT:

This product is in compliance with the U.S. Toxic Substances Control Act (TSCA) inventory requirements.

SARA TITLE III, SECTION 313:

CLEAN AIR ACT (CAA):

CLEAN WATER ACT (CWA):

CALIFORNIA PROPOSITION 65:

MASSACHUSETTS RIGHT TO KNOW:

Not Listed

67-17-5

 PENNSYLVANIA RIGHT TO KNOW:
 CAS# 67-17-5
 9005-65-6

 NEW JERSEY RIGHT TO KNOW:
 CAS# 67-17-5
 9005-65-6

SECTION 16 - OTHER INFORMATION

Format and Preparation Complies with ANSI Z400.1-1993

DISCLAIMER: This brief provides a general overview of the safety data sheet requirements in the Hazard Communication Standard (see 29 CFR 1910.1200(g) and Appendix D of 29 CFR 1910.1200). It does not alter or determine compliance responsibilities in the standard or the Occupational Safety and Health Act of 1970. Since interpretations and enforcement policy may change over time, the reader should consult current OSHA interpretations and decisions by the Occupational Safety and Health Review Commission and the courts for additional guidance on OSHA compliance requirements. Please note that states with OSHA-approved state plans may have additional requirements for chemical safety data sheets, outside of those outlined above. For more information on those standards, please visit: http://www.osha.gov/dcsp/osp/statestandards.html.